



Product Specification Report

Rev. 1.1

BIG ORANGE LIQUID NEW is an excellent degreaser, cleaner and deodorizer based on terpenes with a pleasant orange fragrance. Rinsable with water.

BIG ORANGE LIQUID NEW

Natural based liquid solvent

FEATURES:

Natural base	Based on natural citrus extracts
Easy to remove	Because of its hydrophilic nature it can be rinsed easily with water
Degreases	Effective degreasing action on different types of greasy and oily substances
For solar panels and photovoltaic plants	Can be used for efficient cleaning of the external parts of solar panels

SPECIFICATIONS:

FormLiquid
ColourLight yellow
Odour.....Orange
Density at 20 °C0,86 g/cm³
Flash point.....43°C
Solubility in waterSoluble
VOC85%

ACTIVE INGREDIENTS:

- ✓ Terpenes
- ✓ Emulsifiers

PRECAUTIONS FOR USE:

When used for drains, make sure that the water in which the product was placed is properly treated before discharge into the sewer. For more information refer to the MSDS.

COMPATIBILITY:

Do not use together with acid drain openers. Can damage some types of plastics, rubber or painted surfaces. A preliminary test is recommended.

INSTRUCTIONS FOR USE:

The product can be used diluted or undiluted, depending on the application.

Concrete floors: manually apply the product (undiluted or with a maximum dilution of 1:65). Rub if necessary. Rinse with water and dry if necessary.

Greasy equipment: Apply undiluted on the greasy parts. Rub to emulsify the dirt, and then rinse with a pressure or steam washer.

Drains and grease traps: To clear blocked drains, pour 50 ml of product in the drain. Leave for at least one hour, and then rinse with an abundant amount of hot water. To prevent the formation of grease deposits that can create occlusions, pour 50 to 100 ml of product every week, let it act for one hour and rinse abundantly with hot water.

Odour control: Prepare a 1:30 solution with water. Spray this solution evenly on waste, bins and machinery for waste treatment.

Graffiti: Prepare a solution with 3 parts of water. Apply with a sprayer and let it act 5 to 10 minutes. Rub with a brush and rinse with a pressure washer.

Solar panels: Dilute the product 1:100. Spray on the panels and let it act 2 – 5 minutes. Rinse thoroughly using a pressure washer.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.

IT
Zep Italia s.r.l.
T • 800 016 918
Numero Verde Tecnico
800-579185
a tecnico@zepeurope.com
www.zep.it

UK
Zep UK Ltd.
T • 0151 422 1000
F • 0151 422 1011
info@zep.co.uk
www.zep.co.uk

BE
Zep Industries BV
T • 02 347 01 17
F • 02 347 13 95
sales@zep.be
www.zepindustries.be

NL
Zep Industries BV
T • 0164 250100
F • 0164 266710
info@zepbenelux.com
www.zepindustries.nl

DE
Zep Industries BV
T • 0521 174158
F • 0521 5217114
sales@zepbenelux.com
www.zepindustries.de